

Batteries CYCLON

Plomb étanche spirale longue durée de vie



CYCLON 2V SINGLE CELL:

Products (capacity)	Dimensions					Performance				
	Diameter in. (mm)	Height in. (mm)	Height with terminals in. (mm)	Weight oz. (gm)	Tabs in. (mm)	Constant current discharge/amps* (Constant power discharge/watts per cell)*				
						15 min.	60 min.	90 min.	5 hr.	10 hr.
D cell (2.5Ah)	1.35 (34.3)	2.41 (61.2)	2.68 (68.1)	6.28 (178.0)	.187 x .025 (4.75 x 0.64)	5.9 (11.6)	1.9 (3.8)	1.4 (2.7)	.48 (.94)	.26 (.50)
DT cell (4.5Ah)	1.35 (34.3)	3.78 (96.0)	4.05 (102.9)	9.68 (274.4)	.187x .025 (4.75 x 0.64)	11.2 (21.0)	3.7 (7.1)	2.6 (5.1)	.85 (1.7)	.45 (.90)
X cell (5.0Ah)	1.75 (44.5)	2.87 (72.9)	3.21 (81.5)	12.77 (362.0)	.250 x .025 (6.35 x 0.64)	13.2 (23.9)	3.9 (7.8)	2.8 (5.6)	.96 (1.9)	.50 (1.0)
E cell (8.0Ah)	1.75 (44.5)	3.94 (100.1)	4.28 (108.7)	17.28 (489.9)	.250 x .025 (6.35 x 0.64)	19.0 (35.5)	6.2 (12.4)	4.4 (8.9)	1.6 (3.1)	.81 (1.6)
J cell (12.0Ah)	2.04 (51.8)	4.85 (123.2)	5.34 (135.6)	29.60 (839.2)	0.312 x 0.032 (7.92 x 0.81)	29.4 (53.4)	9.2 (18.3)	6.5 (13.2)	2.3 (4.7)	1.20 (2.3)
BC cell (25Ah)	2.57 (65.3)	6.25 (158.8)	6.82 (173.2)	58.88 (1669.2)	M6 (-) and M8 (+) terminals	54.3 (105.5)	19.3 (36.8)	14.0 (25.6)	4.85 (9.20)	2.55 (4.95)

MONOBLOC 4V & 6V:

Products (capacity)	Dimensions					Performance				
	Length in. (mm)	Width in. (mm)	Height in. (mm)	Weight lb. (kg)	Tabs in. (mm)	Constant current discharge/amps* (Constant power discharge/watts per cell)*				
						15 min.	60 min.	90 min.	5 hr.	10 hr.
4V D (2.5Ah)	3.13 (79.5)	1.81 (46.0)	2.75 (69.9)	.80 (.36)	0.187 x .025 (4.75 x 0.64)	5.9 (11.7)	1.9 (3.8)	1.4 (2.7)	.48 (.93)	.26 (.49)
4V X (5.0Ah)	3.80 (96.5)	2.12 (53.8)	3.02 (76.7)	1.62 (.74)	.250 x .025 (6.35 x 0.64)	13.5 (24.2)	4.0 (7.8)	2.8 (5.6)	1.0 (2.0)	.52 (1.0)
4V E (8.0Ah)	3.81 (96.8)	2.13 (54.1)	4.00 (101.6)	2.11 (.96)	0.250 x .025 (6.35 x 0.64)	19.0 (35.5)	6.2 (12.4)	4.4 (8.9)	1.6 (3.1)	.81 (1.7)
6V D (2.5Ah)	4.48 (113.8)	1.81 (46.0)	2.75 (69.9)	1.15 (.52)	0.187 x .025 (4.75 x 0.64)	5.9 (11.7)	1.9 (3.8)	1.4 (2.7)	.48 (.93)	.26 (.49)
6V X (5.0Ah)	5.48 (139.2)	2.12 (53.8)	3.02 (76.7)	2.16 (.98)	0.250 x .025 (6.35 x 0.64)	13.5 (24.2)	4.0 (7.8)	2.8 (5.6)	1.0 (2.0)	.52 (1.0)
6V E (8.0Ah)	5.48 (139.2)	2.13 (54.1)	4.00 (101.6)	3.15 (1.43)	0.250 x .025 (6.35 x 0.64)	19.0 (35.5)	6.2 (12.4)	4.4 (8.9)	1.6 (3.1)	.81 (1.7)